

# SCS

Web: [www.blownfilm.net](http://www.blownfilm.net) / Email: [sales@blownfilm.net](mailto:sales@blownfilm.net) / Tel: (864) 918-1445  
Extrusion and Converting Specialists



## Come see us in booth #S-5292

As representatives of reputable plastic equipment manufactures in China, SCS offers world class equipment at competitive prices to the North American market. Premiering as an exhibitor at the PACK EXPO in Las Vegas – October 15-17<sup>th</sup> 2007, we will be exhibiting a pouch bag machine and slitting machine as shown below. SCS is located in Greenville, South Carolina and is the North American representative to various manufactures of film extrusion lines, bag machines, stand-up pouch machines, and corona treaters. At PACK EXPO, we will be demonstrating the latest models of our servo-driven multi-functional pouch bag machine as well as a PLC controlled shaftless slitting machine.

SCS IS OFFERING A PRE-SALE OF BOTH POUCH BAG AND SLITTING MACHINES (FOB: Las Vegas)

Please contact us at (864)918-1445 or visit [www.blownfilm.net](http://www.blownfilm.net) for more information.



Equipped with a three-servo drive system, our GSD-60SZLV pouch bag machine offers high production outputs of up to 140 shots/min for three-side-seal bags. This machine is most suitable to handle laminated film of all kinds and provides the ability to produce various bag types and widths ranging from 75mm to 600mm.

Film materials: Laminated hot-seal film  
Roll size: Max. width 1240mm Max.  $\phi$  600mm  
Film feed mechanism: Triple AC servo motor drive system  
Bag length: 2-strike 300mm max. 1-strike 500mm max.  
Bag output: Standing pouch with zipper seal: Max. 70 shots/m  
Standing pouch only: Max 120 shots/min.  
Three-side-seal bag: Max. 140 shots/min

SCS will also have on display a high speed computer controlled slitting machine that can process a wide variety of film types. With a working width of 500mm to 1300mm, this shaftless slitting machine provides for quick roll change over and allows for automatic slow down and stop presets.



Materials: LDPE, LLDPE, BOPP, PET, CPP, Laminates Film  
Thickness: 0.015mm - 0.06mm Working Width: 500mm - 1300mm  
Rewind Width: 50mm - 600mm Machine Speed: up to 350m/min